

Turbo 440 D



Gianni
Ferrari





GTM - GSM
15,5-16 hp



GTR
16-21 hp



GTS
22-23 hp



GT
28 hp



TURBO Z
22-40 hp



TURBOGRASS
22-23 hp



PG - SR
22-28 hp



TURBO 1-1W-2-4
28-50 hp



TURBOLOADER
22-44 hp

TECHNICAL FEATURES

▶ Modello	Turbo Z 440 D	
▶ Engine	Diesel	
Fuel	Kubota V1505-T	
Model	40 hp / 1.498 cc.	
Power / Displacement	4 / Liquid	
No. Cylinders / Cooling	Pressure lubrication system with gear pump – cyclone-type air filter – fuel filter	
Fittings	43 L	
Fuel tank capacity		
▶ Hydrostatic transmission	Danfoss variable displacement axial piston pumps	
Pumps	Danfoss axial piston motors on reduction gears	
Motors	2WD	
Driving wheels	18 km/h	
Max forward speed	Zero Turning Radius (ZTR)	
Driving system	2 control levers with Easy Control Panel (ECP™)	
Brakes	Hydrostatic service brake (neutral position). Dual disc parking brake on transmission	
▶ Seat	Delux Grammer seat with lumbar support and headrest. Adjustable armrest and backrest	
Model	Parallelogram suspension with 3 adjustable height position and driver's weight adjustment (50 kg to 130 kg)	
Seat suspension		
▶ Wheels/Tyres	Front Turf tyres 24 x 12.00 - 12	
Front Turf tyres	Front bar tread tyres (optional) 24 x 12.00 - 12	
Front bar tread tyres (optional)	Oscillating rear axle 13 x 6.50 - 6	
Oscillating rear axle		
▶ Power Take-Off	Mechanical, with PTO shaft / Electric engagement by PTO button	
Type / Engagement		
▶ Front lift	Hydraulic with 2 hydraulic rams	
Type		
▶ Electrical system	12 V / 70 Ah – battery isolator master switch as standard	
Battery	EEC European Standard / ISO	
Safety sensors	Hour meter – coolant temperature	
Standard equipment	Engine oil pressure – coolant temperature – battery (alternator fault) – glowplug – parking brake	
Warning system	As standard	
On-road use equipment		
▶ Weight and measures (tractor unit only, basic version)	Unloaded weight 800 kg	
Unloaded weight	Length / Width / Height 247 x 142 x 132 (200)* cm	
Length / Width / Height		

* with ROPS folded down (upright)

The availability of models, versions and trim may vary depending on the country.

ATTACHMENTS

▶ 160 Dual-Cut™ mulching / rear discharge deck	Cutting width / No. Blades 155 cm (61") / 3 blades	
Cutting width / No. Blades	Quick adjustment with SA™ lever, 2 cm to 8 cm	
Cutting height adjustment	Hydraulic	
Vertical position	200 kg	
Weight		
▶ Side discharge deck	Cutting width / No. Blades 150 cm (59") / 3 blades	
Cutting width / No. Blades	Quick adjustment with SA™ lever, 2 cm to 8 cm	
Cutting height adjustment	Hydraulic	
Vertical position	140 kg	
Weight		
▶ Rear discharge deck	Cutting width / No. Blades 165 cm (65") / 4 blades	
Cutting width / No. Blades	Quick adjustment with SA™ lever, 2 cm to 8 cm	
Cutting height adjustment	Hydraulic	
Vertical position	190 kg	
Weight		
▶ Flail mower	Cutting width / Blade reel 150 cm (59") / 100 flails (50 pairs)	
Cutting width / Blade reel	2 cm to 9 cm	
Cutting height adjustment	240 kg	
Weight		
▶ Aerator / dethatcher	Working width / Blade reel 100 cm (40") / 28 mobile blades	
Working width / Blade reel	90 kg	
Weight		
▶ Snow blade	Working width / Angling 175 cm (69") / ± 30°, hydraulic	
Working width / Angling	140 kg	
Weight		

